

# AIP/DIP Audio Interface Panels



Convert Tascam™ DB25 to XLR or BNC connections for Today's Demanding Audio Requirements



DIP-100



DIP-100R75



AIP-100

## Description:

The AIP/DIP Series Audio Interface Panels from BDI are the perfect solution for cleaning up wiring and reducing the reliance on traditional snake cables for neat and fast interface to modern audio equipment. Available in several styles:

DIP-100 Series— 110 Ohm AES3 XLR and/or 75 Ohm BNC I/O to DB25 connector

AIP-100 Series— Analog XLR I/O interface to DB25 Tascam™ Standard Pin Configuration

ADP/DAP Combination Series— Mix Digital and Analog I/O on a single panel

Designed to interface to all BDI **Audio Toolbox Series** products but can be used with other manufacturer's products conforming to the AES and Tascam™ standards. Provides a 1 RU interface for compact and neat installations. These high quality panels are made from gold contact XLR and DB25 connectors and a rugged steel rack panel. Each panel is supplied with the appropriate 3 ft./ 1 Meter DB25 Male/Female interface cable.

™Tascam is a trademark of Teac Corporation

# Technical Specifications/Model List

## Model

## Description

AIP-100	1 set of 8 XLR Female and 1 set of 8 XLR Male Connectors
ADP-100	1 Set of XLR Analog Female Input and 1 set of XLR AES3 I/O
ADP-100B75	1 Set of XLR Analog Female Input and 1 set of 75 Ohm BNC I/O AES Standard Digital Audio Interface
DAP-100	1 Set of XLR Analog Male Output and 1 set of XLR AES3 I/O
DAP-100B75	1 Set of XLR Analog Male Output and 1 set of 75 Ohm BNC I/O AES Standard Digital Audio Interface
DIP-100	2 sets of 8 XLR AES3 Male/Female I/O
DIP-100B50	2 sets of 50 Ohm BNC I/O for BDI Audio Toolbox series products
DIP-100B75	2 sets of 75 Ohm BNC I/O for AES standard Digital Audio Interface

## Specifications:

XLR Interface	Gold XLR panel mount connector with standard lock/release tab
BNC Interface	75 or 50 Ohm BNC connector with ground lift
Physical	19" L X 1.75" H Standard EIA Rack Mount with four mounting holes
Environmental	0-60 Degrees Celsius non condensing storage and operating environment
Shipping Weight	4 lbs. including shipping carton—carton dimensions 25" L X 4" W X 4" H

